

**TECHNI GL 96**

*Galvaniz Spiraller / Galvanised Spiral Hose*



**-5 / +600 C°**

**Özellikler :**

- Galvaniz sacdan mamül spiraller
- -5°C +600 °C ye dayanıklı

**Features :**

- Spiral hoses made of galvanised metal
- Operating temperature: -5C+600C

**Kullanım Alanları:**

- Egzos Spiral: Dar hatveli, jeneratör egzoz gazı tahliyesinde, dizel araçlarda titreşimi önlemede ve kablo muhafazasında
- Saç Spiral : Geniş hatveli, şöminelerin duman tahliyesinde ve ısı dağıtımında, havalandırma bacalarında, ankraj borusu olarak

**Using Areas:**

- Exhaust spiral: Narrow pitch, for the extraction of exhaust fumes, for the prevention of vibration on the vehicles and for the protection of the cables.
- Galvanised spiral: For the suction and discharge of fumes in the heating systems and for ventilation purposes

İÇ ÇAP INNER DIAMETER	ÜRÜN KODU PRODUCT CODE	FİYAT PRICE	ÜRÜN KODU PRODUCT CODE	FİYAT PRICE
	EGZOS / EXHAUST		HAVALANDIRMA / VENTILATION	
<i>inch</i>		<i>€/m</i>		<i>€/m</i>
30	96-01-E30	13,35	96-01-H30	-
35	96-01-E35	13,93	96-01-H35	-
40	96-01-E40	14,51	96-01-H40	7,54
50	96-01-E50	15,09	96-01-H50	8,13
60	96-01-E60	15,67	96-01-H60	8,70
70	96-01-E70	16,25	96-01-H70	9,29
76	96-01-E76	16,83	96-01-H76	-
80	96-01-E80	17,42	96-01-H80	9,87
90	96-01-E90	17,99	96-01-H90	10,45
100	96-01-E100	19,15	96-01-H100	11,61
110	96-01-E110	20,31	96-01-H110	12,77
120	96-01-E120	22,64	96-01-H120	13,93
130	96-01-E130	23,80	96-01-H130	15,09
140	96-01-E140	25,54	96-01-H140	16,25
150	96-01-E150	27,28	96-01-H150	17,42
160	96-01-E160	29,03	96-01-H160	17,99
170	96-01-E170	31,35	96-01-H170	18,58
180	96-01-E180	-	96-01-H180	19,74
200	96-01-E200	-	96-01-H200	23,22
230	96-01-E230	-	96-01-H230	30,19
250	96-01-E250	-	96-01-H250	34,83
300	96-01-E300	-	96-01-H300	40,64