

TECHNI PVC 59
Ağır Hizmet Verici Hortum / Heavy-Duty Absorptive Delivery Hoses

-20 / +65 C°
Özellikler :

- Emici verici olarak kullanılabilir
- Sert PVC spiraller maksimum esneklik ve kırılmaya karşı dayanıklı
- -20°C ile +65°C durağan halde
- -5°C ile +43 °C hareketli halde

Kullanım Alanları:

- Tarımda, sanayide, inşaatlarda, evlerde her türlü sıvı, çamurlu su, kanalizasyon, gübre ve hafif kimyasalların emiş ve tahliyesinde kullanılır.

Features :

- Can be used as a sucker and a transmitter
- Hardened PVC spirals are durable against flexibility and break
- -20°C and +65°C Static Conditions
- -5°C and +43°C Dynamic Conditions

Using Areas:

- Used for unloading and sucking of any kind of liquids, water with mud and low chemicals.

ÜRÜN KODU PRODUCT CODE	İÇ ÇAP INNER DIAMETER	ÇALIŞMA BASINCI WORKING PRESSURE	VAKUM VACUUM	B.YARI ÇAPI BENDING RADIUS	AĞIRLIK WEIGHT	UZUNLUK LENGHT	FİYAT PRICE
	mm	bar	bar	mm	gr. / mt.	mt.	€/m
59-01-19	19	8	900	95	335	50	1,68
59-01-25	25	8	900	125	400	50	2,00
59-01-32	32	7	900	160	580	50	2,90
59-01-38	38	7	900	190	680	50	3,40
59-01-51	51	6	900	250	970	50	4,85
59-01-63	63	5,5	900	315	1405	50	7,03
59-01-76	76	4	900	375	1680	50	8,40
59-01-90	90	4	900	425	2055	25	10,28
59-01-102	102	4	900	500	2600	25	13,00
59-01-127	127	4	900	625	4000	25	20,00
59-01-152	152	4	900	850	5200	25	26,00
59-01-203	203	4	900	1000	8500	6	42,50

TECHNI PVC 60
Yakıt/Yağ Orta Hizmet Emici&Verici Hortum / Oil-Fuel Absorptive Delivery Hoses (Medium Duty)

-20 / +65 C°
Özellikler :

- Emici verici olarak kullanılabilir
- Sert PVC spiraller maksimum esneklik ve kırılmaya karşı dayanıklı
- -20°C ile +65°C durağan halde
- -5°C ile +43 °C hareketli halde

Kullanım Alanları:

- Petrol ve petrol ürünlerinde (yakıt,motorin,yağlama yağları, parafin vb.) emişve tahliyesinde kullanılır.

Features :

- Can be used as a sucker and a transmitter
- Hardened PVC spirals are durable against flexibility and break
- -20°C and +65°C Static Conditions
- -5°C and +43°C Dynamic Conditions

Using Areas:

- Used for unloading and sucking of petrol and its derivatives (gasoline, diesel fuel, oil, paraffine)

ÜRÜN KODU PRODUCT CODE	İÇ ÇAP INNER DIAMETER	ÇALIŞMA BASINCI WORKING PRESSURE	VAKUM VACUUM	B.YARI ÇAPI BENDING RADIUS	AĞIRLIK WEIGHT	UZUNLUK LENGHT	FİYAT PRICE
	mm	bar	bar	mm	gr. / mt.	mt.	€/m
60-01-19	19	6	800	114	360	50	2,25
60-01-25	25	6	800	150	480	50	3,00
60-01-32	32	5	800	192	580	50	3,63
60-01-38	38	4	800	228	670	50	4,19
60-01-51	51	4	800	300	975	50	6,10
60-01-63	63	4	800	378	1350	50	8,44
60-01-76	76	3	800	450	1700	50	10,63
60-01-90	90	3	800	520	2100	25	13,13
60-01-102	102	3	800	600	2600	25	16,25